


According to Regulation (CE) n<sup>•</sup> 1907/2006



#### 2.3 Other Hazards



According to Regulation (CE) n<sup>•</sup> 1907/2006



#### FLUXO P578AERO Product 01/01/2015 **Revision** 1 2/6 Date Page

#### **SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

#### 3.1 Mixtures

Substance Name	N° CAS N° CE	Classification (1272/2008)	Concentration (%)
Propellant : Isobutane Propane Butane	75-28-5 - 200-857-2 01-2119485395-27 74-98-6 - 200-827-9 01-2119486944-21 106-97-8 - 203-448-7 01-2119474691-32	Flam. Gas 1 H220 Press. Gas	> 30
Aliphatic hydrocarbons	64742-47-8 265-149-8 01-2119456620-43	Asp. Tox. 1 (H304)	> 50
Ethoxylate Alcool	68131-40-8	Acut Tox Cat 4 (H302) Eye Dam. Cat 1(H318)	2,5 – 10

Full Test of H phrases: see section 16.

#### **SECTION 4 – FISRT AID MEASURES**

#### 4.1 Description of first aid measures

General information	Take off immediately all contaminated clothing and wash it before reuse. In case of accident or unwellness, seek medical advice immediately (show directions for
	use or safety data sheet if possible). If unconscious place in recovery position and seek medical advice.
After ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell.
After eye contact	In case of eye irritation consult an ophthalmologist. Rinse immediately carefully and thoroughly with eye-bath or water.
After skin contact	After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation. Consult a physician. Take off immediately all contaminated clothing.
Following inhalation	In case of inhaling spray mist, consult a doctor immediately and show him packing or label. If breathing is irregular or stopped, administer artificial respiration

4.2 Most important symptoms and effects, both acute and delayed Respiratory complaints Drowsiness

4.3 Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5 – FIREFIGHTING MEASURES**


5.1 Extinguishing media

Suitable extinguishing media: Water spray Water mist Foam Extinguishing powder Unsuitable extinguishing media: Full Water Jet

5.2 Special Hazards arising from the substance or mixtures



According to Regulation (CE) n<sup>•</sup> 1907/2006



#### 7.1 Precautions for sage handling

All work processes must always be designed so that the following is excluded: Inhalation Skin contact Eye contact Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

# 7.2 Conditions for safe storage, including any incompatibilities Ensure adequate ventilation of the storage area. Hints on storage assembly: Materials to avoid oxidizing agent Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place.

7.3 Specific End Uses

: Fluorescent Penetrant for Penetrant Testing

#### SECTION 8 - EXPOSURE CONTROLES AND PERSONAL PROTECTION

#### 8.1 Control Parameters


Component	CAS	
Aliphatic hydrocarbons	64742-47-8	Long Term Value = 1000 ppm Short Term Value = 1500 ppm
Butane	106-97-8	Long Term Value = 800 ppm = 1900 mg/m3

#### 8.2 Exposure Controls

Eye/face protection	: Suitable eye protection: Eye glasses
Skin protection	: Use protective skin cream before handling the product. Hand protection
	Suitable gloves type: NBR (Nitrile rubber)
Respiratory protection	: Filter type: AX
Protective clothing	: Body protection: not required.
	General health and safety measures: When using do not eat, drink, smoke, sniff.
	Wash hands before breaks and after work. After cleaning apply high-fat content
	skin care cream.



According to Regulation (CE) nº 1907/2006



#### 9.2 Others information

#### SECTION 10 - STABILITY AND REACTIVITY

#### 10.1 Reactivity

: Reaction with oxidising agent		
: Stable in normal condition of use		
ons		
: No Data available		
: No Data available		
: No Data available		
10.6 Hazardous decomposition products		
: No Data available		

#### SECTION 11 – TOXICOLOGICAL INFORMATION

#### 11.1 Information on Toxicological Information

Component	DL50 Oral	DL50 Dermal	CL50 Inhalation
Aliphatic hydrocarbons	> 2000 mg/kg (rat)	> 5000 mg/kg (lapin)	> 5000 mg/m <sup>3</sup> (rat)

Acute oral toxicity: Data apply to the main component. Acute dermal toxicity: Data apply to the main component. Acute inhalation toxicity: Data apply to the main component.


### SECTION 12 – ECOLOGICAL INFORMATION

#### 12.1 Toxicity

Component	EL50 (24h) daphnie	LL50 (96h) poisson
Aliphatic hydrocarbons	> 1000 mg/L	> 1000 mg/L



According to Regulation (CE) n<sup>•</sup> 1907/2006



#### SECTION 15 – REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance/mixture

15.2 Chemical Safety Assessment

: No data available

#### **SECTION 16 – OTHER INFORMATION**

The European regulation imposes that all the H sentences (section 2) appear in this paragraph. According to their concentration in the final product, these sentences do not appear on the label. This is why sentences or initials appearing in this paragraph can not appear on the label.

#### H sentences (section 2 and 3)

H220 : Extremely flammable Gas



According to Regulation (CE) n<sup>•</sup> 1907/2006



01/01/2015

Date

## Product FLUXO P578AERO

Revision 1

- H222 : Extremely Flammable Aerosol
- H229 : Pressurised container : May burst if heated
- H302: Harmful if swallowed
- H304: May be fatal if swallowed and enters airways
- H318: Causes serious eye damage

Use

: Please refer to Technical Data Sheet